

Star Series Specifications



Orion 4-Star pH/ISE

Portable Meter (Cat. No. 1215000)
Portable Meter Kit (Cat. No. 1215001)

- Durable, waterproof, IP67 meter stands up to the most demanding field applications while delivering over 2,000 hours of continuous operation.
- Ergonomic design for comfortable handling
- Accepts ISFET (Ion Selective Field Effect Transistor) electrodes
- SMART STABILITY™ and SMART AVERAGING™ functions for automatically optimized accuracy, precision and response time
- Storage of up to 10 password protected methods for easy retrieval of operation procedures
- Simultaneous display of pH or ISE and temperature measurements

Specifications	
pH	
Readout Range / Resolution	-2.000 to 19.999 or 0 to 14 in aqueous solutions / 0.1,0.01,0.001
Relative Accuracy	± 0.002
SMART STABILITY™ and SMART AVERAGING™	Resolution dependent / automatic
AUTO-CAL™ and/or Manual Calibration	1 to 5 points; US/NIST, DIN, and custom buffers recognized
ISE	
Range / Resolution	0 to 19900 / 1,2, or 3 significant digits
Relative Accuracy	± 0.2 mV or 0.05%, whichever is greater
SMART STABILITY™ and SMART AVERAGING™	Resolution dependent / automatic
Units	M, mg/L, %, ppb, or no units
# ISE Cal points	1 to 5
Special ISE Calibration Features	Linear point to point, selectable auto-blank non-linear, low concentration range
mV	
Range – mV / RmV	± 1999.9
ORP	E _H autocalibration to standard hydrogen electrode
Resolution	0.1
Relative Accuracy	± 0.2 mV or 0.05%, whichever is greater
Temperature	
Range / Resolution	-5 to 105 °C / 0.1 up to 99.9 °C, 1.0 over 99.9 °C
Relative Accuracy	± 0.1 °C
Temperature Compensation	Auto/Manual
Display	Custom backlit LCD, for easy viewing
Inputs/Outputs	
Sensor Inputs	pH/ISE - BNC; ATC-miniDIN-Locking; Reference-Pin tip (all waterproof)
Solid State pH Sensor	ISFET - miniDIN - locking
Communications	Waterproof bi-directional RS232 - Stereo jack, optional USB interface Cable
Special GLP Software Features	
# Of Data Logging Points	200 points by time, stability or manual read with time/date stamp
Calibration Log	Last 10 Calibrations
User Method Storage	10 Saved
Advanced Self-test and Diagnostics	YES
GLP Electrode Verification	YES
Password Protection	YES
Internet Software Updates / Downloadable Methods	YES
21 CFR Part 11 Software Package	Optional
Power	4 x AA batteries, powerless date protection
Regulatory and Safety	CE, CSA, UL, TÜV, FCC Class A limits
Environmental Operating Conditions	
Ambient Operating Temperature	5 to 45 °C
Relative Humidity	5 to 85% Non-Condensing
IP Rating	IP67, waterproof and dustproof
Warranty	36 months (from date of purchase)

Above data generated under optimal/controlled circumstances.

Note: ISFET capability available in Fall 2005

pH/ISE Portable Meter Kit (1215001) Includes:

Cat. No.	Description
1215000	4-Star pH/ISE portable meter
9107BNMD	Low maintenance Triode™ pH/ATC electrode
910060	pH storage solution, 5x60 mL
1210004	Hard field case
910410	pH 4.01 buffer, 10 pack
910710	pH 7.00 buffer, 10 pack
911010	pH 10.01 buffer, 10 pack

Star Series Specifications

Orion 4-Star**pH/ISE**

Portable Meter (Cat. No. 1215000)

Portable Meter Kit (Cat. No. 1215001)

(page 2 of 2)